



BIKE RACK

APRIL 2021

SHEET 1 OF 1

NOTE:

- 1) BE LOCATED AND ANCHORED TO A SOLID, IMMOVABLE STALL SURFACE AND INSTALLED VERTICALLY PLUMB IN TWO PLANES
- 2) BE AN 'INVERTED U' TYPE OR EQUIVALENT, WHICH SUPPORTS THE BICYCLE UPRIGHT BY ITS FRAME IN TWO PLACES
- 3) BE AT LEAST 18 INCHES WIDE AND 33 INCHES TALL WHEN INSTALLED; BE UNIFORMLY ALIGNED AND EVENLY SPACED; BE CENTERED IN A POURED FOUNDATION 'DESIGN STALL' WITH A MINIMUM DIMENSION OF 36 INCHES BY 72 INCHES; AND BE AT LEAST 24 INCHES FROM ANY WALL OR OTHER OBSTRUCTION
- 4) RACK(S) FASTENED TO DESIGN STALL FOUNDATION USING 8 INCH J BOLTS IN 12 INCH DEEP HOLE
- 5) NOT RESULT IN TRIPPING HAZARD
- 6) PREVENT THE BICYCLE FROM TIPPING OVER
- 7) ENABLE THE FRAME OR BOTH WHEELS TO BE SECURED
- 8) SUPPORT BICYCLES WITHOUT A DIAMOND-SHAPED FRAME
- 9) ALLOW A U-LOCK TO LOCK ONE WHEEL AND A FRAME TUBE OF AN UPRIGHT BICYCLE
- 10) RESIST BEING CUT OR DETACHED USING HAND TOOLS

